

REMS Push

Hand pressure testing pump

Proven, reliable testing pump for pressure and tightness tests of piping systems and receptacles.

Testing and pressure range $p \leq 60 \text{ bar}/6 \text{ MPa}/870 \text{ psi}$

Water, oil, glycol

pH-value of liquids 7 – 12

Temperature of liquids -30° to 60°C

Viscosity of liquids $\leq 1.5 \text{ mPa s}$

REMS Push – reliable pressure hold.

Universal use

For plumbing, heating, solar system and sprinkler installations, for compressed air, steam and cooling systems, oil installations, for boiler and pressure vessel building.

Execution

Robust, job-site proven metal design for tough use. REMS Push with corrosion-resistant, powder-coated 12 ltr steel tank. Distortion resistant lever with ergonomic handle, doubles as carrying handle when locked. Wear resistant pressure piston in brass, $\varnothing 30 \text{ mm}$. High-pressure hose with $\frac{1}{2}''$ -connection. Fine scale pressure gauge (accessory), $p \leq 16 \text{ bar}/1.6 \text{ MPa}/232 \text{ psi}$, for reading a pressure change of 0.1 bar for tightness testing according to DIN 1988, as accessory.

Stainless steel tank

REMS Push INOX with 12 ltr stainless steel tank. For extremely long life.

Functioning

Pressure and tightness test with water or oil. Double valve system for reliable pressure built-up, with rust-proof steel balls. High pumping capacity with long stroke, fine pressure adjustment at short pushes. High pressure hose with fabric ply prevents measurement errors.



Supply format

REMS Push. Hand pressure testing pump with pressure gauge, $p \leq 16 \text{ bar}/1.6 \text{ MPa}/232 \text{ psi}$, for pressure and tightness testing of piping systems and receptacles up to $60 \text{ bar}/6 \text{ MPa}/870 \text{ psi}$, Corrosion-resistant, powder-coated 12 ltr steel tank. 1.5 m high-pressure hose with $\frac{1}{2}''$ -connection. In cardboard box.

	Art.-No.	
	115000	



Supply format

REMS Push INOX. Hand pressure testing pump with pressure gauge, $p \leq 16 \text{ bar}/1.6 \text{ MPa}/232 \text{ psi}$, for pressure and tightness testing of piping systems and receptacles up to $60 \text{ bar}/6 \text{ MPa}/870 \text{ psi}$. 12 ltr stainless steel tank. 1.5 m high-pressure hose with $\frac{1}{2}''$ -connection. In cardboard box.

	Art.-No.	
	115001	



Accessories

Description	Pressure $p \leq \text{bar}/\text{MPa}/\text{psi}$	Art.-No.
Connecting piece with pressure gauge and shut off valve	60/6/870	115110
Fine scale pressure gauge	16/1.6/232	115045

