

Ultralite® Slabs



Don't be fooled – Ultralite® Slabs look and perform like concrete slabs but at only 13kg they are lightweight and very easy to handle and transport. So give your aching back a rest and use Ultralite® Slabs to mount all your air conditioning units and domestic air source heat pumps.

Features

- Safe working load – 56kg per 50mm diameter
- Easy to handle and transport
- Available in three sizes

Construction

- Encapsulated polystyrene core
- Fibre reinforced cement coating
- Outside slurry coating with texturing

Related Products

Flexi Frames

The Package

- Ultralite® Slab •

Chemical Resistance

In normal usage conditions an equipment pad can be exposed to a variety of chemicals. The Ultralite® Slab has been fully tested in accordance with ASTM D2299 for resistance against: all refrigerants, compressor oils, salt solution and synthetic canine urine.

Freeze/Thaw Testing

The Ultralite® Slab has been independently tested to the rigorous freeze-thaw regimen specified by ASTM C67. This standard dictates a twenty five cycle freeze-thaw sequence. The freeze portion of the sequence takes place with the top surface of the slab under 12mm of water. Once twenty five cycles are complete the slab is examined for cracks and crazing. The Ultralite® Slab performed flawlessly.

* It is the installer's responsibility to ensure that equipment weights do not exceed the safe working loads quoted and that the roof structure onto which these products are being applied is sufficiently sound to withstand the weight and point loading. If these products are used in contact with a PVC roof membrane, the installer should seek advice from the membrane manufacturer on the possible migration of plasticizers, and the effect of this on the roof guarantee. These products should not be used for any purpose other than that for which they have been designed, and the products must not be modified in any way. Pump House accepts no liability for damage caused by the incorrect application or installation of these products.

Part Code	Description	Length	Width	Depth	Safe Working Load*
19551	ULTRALITE® Equipment Slab	610mm	610mm	50mm	270kg
19552	ULTRALITE® Equipment Slab	610mm	1220mm	75mm	265kg