

<b>Product Code</b>	22400, 22401, 22402, 22405, 22407, 22409, 22411.
<b>Description</b>	Un-Insulated Flexible Ducting
<b>Size Range</b>	102, 127, 152, 203, 254, 305, 355mm
<b>Other</b>	
<b>Related Products</b>	Insulated Flexible Ducting

### PRODUCT INFORMATION

## ALU SHINE

### Non - Insulated Aluminium

#### FLEXIBLE AIR DUCTS

ALUSHINE non - insulated aluminium flexible air ducts are specifically produced for low and medium pressure heating, cooling, ventilation, exhaust and air conditioning systems.

Airtight ALU SHINE is produced from multi-layer aluminium and metallized polyester, strengthened with high tension hard steel spring wire.

#### ALUMINIUM LAMINATED BODY & JACKET

- Impermeable to UV rays
- Highly resistant to UV rays
- 98% reflective
- Resistant to chemicals

#### FLEXIBLE & SEAMLESS CONSTRUCTION

#### SMOOTH INNER SURFACE

- Minimal pressure loss

#### HIGH TENSION STEEL WIRE

<b>Approved by:</b>	Approval pending	<b>Issued Date:</b>	Not Approved Yet
<b>Version:</b>	V.3 - 22/05/2012	<b>Review Date:</b>	

### TECHNICAL PROPERTIES

**Construction** – 1 ply aluminium, 2 ply polyester

**Available Diameters** – 82mm – 800mm

**Temperature Range** - -3 °C/ + 150°C

**Air Velocity** – 30 m/s (max)

**Operating Pressure** - 3000 pa (max)

**Standard Length** – 10m

**Packing** – Single Cardboard Box

**Certificate;**

**United Kingdom** – BS 476 PART 6&7

**Russia** – GOST-R

<b>Approved by:</b>	<b>Approval pending</b>	<b>Issued Date:</b>	<b>Not Approved Yet</b>
<b>Version:</b>	<b>V.3 - 22/05/2012</b>	<b>Review Date:</b>	